



TECHNICAL DATA SHEET

Product Name

SCG LDPE

Product Type

Autoclave LDPE for Extrusion Coating/Lamination

Product Grade

D388C

Product Description

SCG LDPE D388C is an autoclave low density polyethylene grade for extrusion coating/lamination with with good processability and good organoleptic.

Typical Application

- For general use in extrusion lamination and extrusion coating
- For coating on different substrates; Aluminum foil, Nylon, PET, OPP, Paper etc.
- Food and non-food packaging

Product Characteristics

- Excellent draw ability
- Outstanding organoleptic
- Good processability
- Good thickness control with low coating weight

International Compliance

- U.S FDA 21 CFR 177.1520
- Regulation (EU) No.10/2011
- Regulation (EC) 2023/2006 (GMP)
- Packaging and Packaging waste Directive 94/62/EC

Note: Direct food contact is subjected to the extraction provisions of the regulation on the finished food contact package

Physical Properties

Property	Test Method	Typical Value	Unit
Resin Properties			
Melt Flow Rate	ASTM D 1238 @ 190°C, 2.16 kg	8.0	g/10 min
Density	ASTM D 1505	0.919	g/cm ³
Melting Point	ASTM D 2117	107	°C
Vicat Softening Point	ASTM D 1525	90	°C
Coating Property			
Neck-in	TPE Method	15	cm

Coating property obtained by SCG internal laboratory coating with melt temperature 315°C, Die width 350 mm, Die lip 1.5 mm

Note: the given values are typical value measured on the product. Values herein are not to be constructed as a product specification.

SCG Performance Chemicals Co., Ltd.





TECHNICAL DATA SHEET

Product Name

SCG LDPE

Product Type

Autoclave LDPE for Extrusion Coating/Lamination

Product Grade

D388C

Processing Guidelines

SCG LDPE D388C is recommended to apply primer or corona treatment on substrate before coating for better adhesion. The actual processing condition depends on each machine type, size, and thickness. Generally, melt temperature should be around 300-330°C. Minimum air gap 150 mm is recommended.

Product Technical Assistance

For technical assistance or further information on this product or any other SCG Chemicals' products contact your SCG Chemicals technical service at the address or telephone number as specified below.

Product Available Form

- Pellet

Product Packaging

- 25 kg loose bag
- 25 kg stretch wrap palletized
- 750 kg big bag
- Seabulk container

Storage

- Store in original container in tidy according to the manual of Handling and Storage from Thai Polyethylene Company Limited/ Thai Polypropylene Company Limited.
- Product(s) should be stored in dry and dust free location at temperature below 50°C and protected from direct sunlight and/or heat, well-ventilated area, away from incompatible materials and food and drink, as this may lead to quality deterioration, which results in odour generation and colour changes and can have negative effects on the physical properties of this product.
- Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
- The storage area should be stable and not be slopped.

SCG Performance Chemicals Co., Ltd.

