

HDPE 7210

YUZEX 7210 is a high density polyethylene resin with good processibility. It offers a high impact resistance combined with good stiffness, high ESCR and low warpage. This resin is particularly suitable for the production of pails and crates. YUZEX 7210 complies with FDA regulation 21 CFR177. 1520.

Application / Use Case

Injection Molding / Bottle cap, Bottle crate

Specification

	Specification	Unit	Test Method
Density	0.960	g/cm ³	ASTM D1505
Melt Index	5.5	g/10min	ASTM D1238

Physical Properties

	Specification	Unit	Test Method
Softening Point(Vicat)	125	°C	ASTM D1525
Tensile Strength at Yield	270	kg/cm ²	ASTM D638
Tensile Strength at Break	100	kg/cm ²	ASTM D638
Elongation at Break(MD)	>500	%	ASTM D638
IZOD Impact Strength(Notched, 23°C)	9	kg cm/cm	ASTM D256
Flexural Modulus	9200	kg/cm ²	ASTM D790
ESCR	4	hr	ASTM D1693
Brittleness Temperature	<-80	°C	ASTM D746

Note : These are **typical properties** only, and are **not to be construed as specifications**. The physical properties are highly dependent on the manufacturing conditions. So customers should performances by their own tests.

ISO 9001 Certified

