

Product Data

TITANLENE LDC800YY FOR EXTRUSION COATING

- CHARACTER** LDC800YY is a low density polyethylene resin for extrusion coating and is a barefoot grade. LDC800YY meets the U.S. Food and Drug Administration (FDA) criteria for food contact use as specified in 21 CFR 177.1520 (c) 2.1 & (c) 2.2.
- APPLICATIONS** Coating for all substrates.
- ADVANTAGES** Good drawdown, good heat sealability and adhesion properties.

<u>TYPICAL RESIN PROPERTIES</u>	<u>UNIT</u>	<u>LDC800YY</u> ^(a)	<u>ASTM METHOD</u> ^(b)
Melt index	g/10 min	3.5	D1238
Density	g/cm ³	0.920	D1505
Vicat softening point	°C	87	D1525
Neck-in (constant output 50m/min, 295°C)	cm	8	(c)
<u>BARRIER PROPERTIES</u>			
MVTR(90%RH, 37.8°C, 25µm)	g/m ² /24h	18	F372
O ₂ GTR	$\frac{10^4 \text{cm}^3 \mu\text{m}}{\text{m}^2 \text{24hr atm}}$	22	D3985

(a) Values shown are typical and are not to be considered as specifications.

(b) ASTM test methods are latest under the Society's current procedures.

(c) Internal method

Processing conditions

Melt temperature : 270 - 340°C

LOTTE CHEMICAL TITAN (M) SDN. BHD.

Titanex® • Titanlene® • Titanzex® • Titanpro® • Titanvene®

塑料专家 www.ponci.com.cn/wxb/ +13538586433 +18816996168

