



# COSMOTHENE<sup>®</sup> EVA VF024N00

## CHARACTERISTICS

**COSMOTHENE EVA VF024N00** is produced by the latest autoclave process technology licensed by Sumitomo Chemical Co. Japan.

**COSMOTHENE EVA VF024N00** offers good processibility, good color stability, transparency and gel control.

## APPLICATIONS

**COSMOTHENE EVA VF024N00** is designed for extrusion sheet use in solar photovoltaic cell encapsulation.

## PHYSICAL PROPERTIES:

ITEM	UNIT	VF024N00	TEST METHOD
Vinyl Acetate Content	Wt. %	28	TPC METHOD
Melt Flow Rate	g/10 min	28	ASTM D1238
Density	g/cm <sup>3</sup>	0.95	ASTM D792
Tensile Strength	MPa	6.1	ASTM D638
Elongation	%	880	ASTM D638
Surface Hardness	Shore D	21	ASTM D2240
Brittleness Temperature	°C	< -50	JIS K7216
Ring & Ball Softening Point	°C	122	ASTM E28
Melting Point	°C	69	TPC METHOD

- The figures presented are typical laboratory averages, only for reference.
- The information is based on our current knowledge, is subjected to continuous updates and is intended to suggest/ recommend product applications and to provide typical data on the related properties. It should not therefore be construed as guaranteeing any specific property of the product. TPC makes no warranty of any kind, expressed or implied, regarding the accuracy of these data.

