

TAIPOL[®]

TAIPOL[®] 6014

Styrene-Ethylene/Butylene-Styrene (SEBS) Block Copolymer

TAIPOL[®] 6014 is a linear triblock copolymer with 18% styrene content.

The product exhibits the following characteristics:

- Medium to low molecular weight
- Superior weather and heat resistance
- Good compatibility with plastics and oils
- Suitable for films, adhesives, sealants, coatings, plastic modification and thermoplastic elastomer compound

TAIPOL[®] 6014 (SEBS) is offered as a porous pellet supplied from Taiwan

Polymer Properties	Test Method	Unit	Typical Value ⁽¹⁾
Diblock Content	TSRC Method	wt%	<1
Specific Gravity	ASTM D792	-	0.91
Hardness	ASTM D2240	Shore A	70
Tensile Strength	ASTM D412	MPa	16
Elongation at Break	ASTM D412	%	500
Solution Viscosity ⁽²⁾	TSRC Method	cP	-

Sales Specification	Test Method	Unit	Range	
			Min	Max
Styrene	TSRC Method	wt%	16.5	19.5
Volatile Matter	TSRC Method	wt%	-	0.5
Ash (w/o AB)	ASTM D5667	wt%	-	0.2
Ash (w/ AB)	ASTM D5667	wt%	-	0.6
Melt Flow Rate ⁽³⁾	ASTM D1238	g/10min	3.0	8.0

1) Not to be construed as specifications

2) 20 wt% in Toluene, 25°C

3) 230°C/2.16kg

