

Date: 11 Sep 2024

Technical Data Sheet for HDPE PIPE AS PER IS 4984:2016				
Pipe Size: PE 100 PN 6 DN 160 SDR 21				
Manufacturer: Reliance Industries Ltd; Brand: RELPIPE				
Sl. No.	Parameter	Units	Clause as per IS 4984:2016	Specified Value
1	Visual Appearance		7.1	Free from grooving and other Defects
2	Dimension of Pipes			
	2.1) Outer Diameter	mm	7.4.1.1	160 mm + 1.2 mm
	2.2) Wall Thickness	mm	7.4.1.1	Min 7.7 mm – Max 8.6 mm
	2.3) Ovality	mm	7.4.1.2	3.2 mm
	Performance Requirements			
3	Hydraulic Characteristics @80°C/5.7Mpa/48 Hours (Acceptance Test)		8.1.1 (Table 5)	No localized Swelling or Leakage during the test period
4	Longitudinal Reversion Test	%	8.2	shall not be greater than 3%
5	Carbon Black Content	%	8.3	2.5± 0.5 %
6	Carbon Black Dispersion	-----	8.3	Dispersion of carbon black shall be Satisfactory
7	Melt Flow Rate	gms/10mins	8.4	(0.2-1.1) MFR shall not deviate from the MFR of the resin by more than 30 percent
8	Density	Kg/m ³	8.7	930-960 Kg/m ³
9	Oxidation Induction Time	Minutes	8.5	Shall not be less than 20 min
10	Elongation at Break	%	8.9	≥ 350 percent
11	Marking on Pipe	-----	10.1	Mfgr's name, Designation of Pipe & Lot Number+ Customer Req

Remarks: The above product meet the requirement of IS 4984:2016 with amendments

Pradeep Gupta
Sales & Marketing

