



Globalene SF7152

Polypropylene Composite Material Alloy 聚丙烯複合材料

Features 特性: • High impact strength 高衝擊強度 • Low shrinkage 低收縮率 • 10%GF reinforced 10%玻璃纖維補強		Typical Application 一般應用: •Injection : 射出成型 Auto parts 汽車零件 Motorcycle part 摩托車零件		
Typical Properties	Test Method	Unit	Value	
一般性質	測試方法	單位	數值	
Melt flow rate (230°C,2.16kg) 熔融流率	ASTM D1238	g/10min	5	
Density 密度	ASTM D792	g/cm ³	0.96	
Tensile strength at yield 降伏點抗張強度	ASTM D638	kg/cm ²	390	
Elongation at yield 降伏點伸長率	ASTM D638	%	5	
Flexural modulus 彎曲彈性係數	ASTM D790	kg/cm ²	19500	
Izod Impact strength, notch 23°C 艾氏衝擊強度, 缺口 23°C	ASTM D256	kg-cm/cm	20	
Heat deflection temperature 熱變形溫度	ASTM D648	°C	155	
Rockwell hardness 洛氏硬度	ASTM D785	R scale	78	
Mold shrinkage 收縮率	ASTM D955	%	0.4	

Product Stewardship Information 產品責任資訊

<p>a. RoHS Directive 歐盟有害物質限制指令 Globalene SF7152 meets the requirements of RoHS Directive 福聚烯 SF7152 符合歐盟有害物質限制指令</p>
<p>b. Chemical Inventories 化學品庫 All ingredients in SF7152 are in compliance with the following chemical inventories : 福聚烯 SF7152 之所有成份均登記於下列化學品庫中： (1) TSCA(U.S.A) (2) DSL(Canada)</p>