



Globalene SG0108

Polypropylene Composite Material Alloy 聚丙烯複合材料

Features 特性: • High impact resistance 高耐衝擊性 • Excellent metalizing 電鍍性優 • Excellent paintability 噴漆性優		Typical Application 一般應用: •Injection : 射出成型 Metalizing/Painting auto/motorcycle parts 電鍍/噴漆 汽機車配件		
Typical Properties	Test Method	Unit	Value	
一般性質	測試方法	單位	數值	
Melt flow rate (230°C,2.16kg) 熔融流率	ASTM D1238	g/10min	6	
Density 密度	ASTM D792	g/cm ³	0.9	
Tensile strength at yield 降伏點抗張強度	ASTM D638	kg/cm ²	230	
Elongation at yield 降伏點伸長率	ASTM D638	%	8	
Flexural modulus 彎曲彈性係數	ASTM D790	kg/cm ²	12000	
Izod Impact strength, notch 23°C 艾氏衝擊強度, 缺口 23°C	ASTM D256	kg-cm/cm	22	
Heat deflection temperature 熱變形溫度	ASTM D648	°C	85	
Rockwell hardness 洛氏硬度	ASTM D785	R scale	63	
Mold shrinkage 收縮率	ASTM D955	%	1.2	

Product Stewardship Information 產品責任資訊

a. RoHS Directive 歐盟有害物質限制指令

Globalene SG0108 meets the requirements of RoHS Directive

福聚烯 SG0108 符合歐盟有害物質限制指令

b. Chemical Inventories 化學品庫

All ingredients in SG0108 are in compliance with the following chemical inventories :

福聚烯 SG0108 之所有成份均登記於下列化學品庫中 :

(1) TSCA(U.S.A) (2) DSL(Canada)