



# 401-NA01

## Product Technical Information

Polypropylene – Impact Copolymer

**401-NA01** is a nucleated low melt flow rate, very high impact copolymer for demanding industrial applications. This nucleated grade allows a faster cooling and excellent dimensional stability. It offers a superior balance of stiffness and impact strength and low gel content compared to competitive impact copolymers of similar melt flow rate.

## Applications

- Corrugated sheet (twin walled sheet)
- Corrugated pipe and fittings
- Sheets for thermforms
- Injection moulding

## Benefits and Features

- Improved impact / stiffness balance
- Very low gel content
- Superior surface quality
- Superior processability

Properties		Test Methods	Values	Units
<b>Physical</b>				
Melt Flow Rate	230°C/2.16kg	ISO 1133	1.2	g/10min
<b>Mechanical</b>				
Flexural Modulus	@ 23°C	ISO 178	1300	MPa
Tensile Strength	@ Yield	ISO 527-1,-2	27	MPa
Izod Impact Strength, Notched	@ +23°C	ISO 180/1A	45	kJ/m <sup>2</sup>
	@ -20°C	ISO 180/1A	7.5	kJ/m <sup>2</sup>
Charpy Impact Strength, Notched	@ +23°C	ISO 179/1eA	50	kJ/m <sup>2</sup>
	@ -20°C	ISO 179/1eA	8	kJ/m <sup>2</sup>



# 401-NA01

## Thermal

Melting Point		ASTM D 3417	165	°C
Vicat Softening Temperature	@ 10 N	ISO 306/A	154	°C
HDT	@ 0.45 MPa	ISO 75/B	91	°C

---

- Data should not be used for specification work