



TUB121B Polyethylene Copolymer

TUB121B is a black high density bimodal polyethylene copolymer designed for extrusion of potable water, natural gas, industrial, and mining pipe. It is listed by the Plastics Pipe Institute (PPI TR-4, as both PE 4710 and PE 100) and is certified to ANSI/NSF Standard 14, ANSI/NSF Standard 61, CSA B137.1 and CSA B137.4.

Typical Properties¹

	Values		ASTM Method
	English Units	SI Units	
Density (Natural)	—	0.9485 g/cc	D4883
Density (Black)	—	0.959 g/cc	D792
Melt Index 190°C/5.0 kg	—	0.30 g/10 min	D1238
Melt Index 190°C/ 21.6 kg	—	8.5 g/10 min	D1238
Compression Molded Sample			
Tensile Strength			D638
@ Yield (2 in/min)	3625 psi	25.0 MPa	
@ Break (2 in/min)	5500 psi	38.0 MPa	
Elongation			D638
@ Break (2 in/min)	>600%	>600%	
Flexural Modulus²	150,000 psi	1,035 MPa	D790
Notched Izod Impact Strength	9 ft-lbf/in	0.49 kJ/m	D256
Hardness (Shore D)	66	66	D2240
Brittleness Temperature	<-180 °F	<-118 °C	D746
Vicat Softening Point	259 °F	126 °C	D1525
Thermal Stability	428 °F min	220 °C min	D2513/D3350
Hydrostatic Design Basis			D2837
@ 23 °C	1600 psi	11.0 MPa	
@ 60 °C	1000 psi	6.9 MPa	
Minimum Required Strength	—	10.0 MPa	ISO 9080
Environmental Stress Crack Resistance³	>5000 hrs	>5000 hrs	D1693
Notch Tensile (PENT)	>10,000 hrs	>10,000 hrs	F1473
Carbon Black Concentration	2.3%	2.3%	D1603
Cell Classification	445574C	445576C	D3350
Oxidative Resistance Classification	CC3	CC3	D3350

¹ Typical properties will vary within specification limits.

² 2% Secant-Method 1

³ Condition C