



ELTEX® TUB120NRG

Product Technical Information

ELTEX® TUB120NRG is a natural high-density polyethylene copolymer, produced by INEOS Innovene-S process, with increased resistance to temperature and designed for the extrusion of a broad range of pipe dimensions, including large diameter and/or high wall thickness.

Benefits & Features

ELTEX® TUB120NRG fulfils the MRS 10 (PE 100) classification in accordance with ISO 12162 as well as PE-RT Type II classification according to ISO 24033, both based on ISO 9080 analysis.

This natural product provides a step-out performance of increased stress cracking resistance and is designed to allow maximum safety under all installation conditions and reduction of installation costs using, for examples, no dig trenchless techniques, sandless laying or other non-conventional installation techniques that may increase the risk of scratches along the pipes.

Applications

- Industrial pressure and non-pressure pipes
- Oil & Gas pipes
- Ducting of High Voltage cables
- Extruded sheets

Properties	Conditions	Test Methods	Values	Units
Rheological				
Melt Flow Rate	190°C/5kg	ISO 1133-1	0.27	g/10min
Physical				
Density	23°C	ISO 17855-2 & ISO 1183-1 (A)	949	kg/m ³
Mechanical				
Flexural Modulus	23°C	ISO 178	1100	MPa
Tensile Strength at Yield	23°C, 50 mm/min	ISO 527-2	25	MPa
Rapid Crack Propagation	0°C, 250 SDR11 pipes	ISO 13477	≥ 10	bar
Strain Hardening Modulus	80°C	ISO 18488	≥ 70	MPa
Thermal				
Oxidation Induction Time (OIT)	210°C	ISO 11357-6	>20	Min
Data should not be used for specification work				



ELTEX[®] TUB120NRG

Storage

The product should be stored in a dry and dust free environment at temperature below 50°C. Exposure to direct sunlight should be avoided as this may lead to product deterioration.

It is advised to process the product within maximum one year after delivery.