Radilon® MIXLOY S RVA80T 100 NT

Radici Group High Performance Polymers - Polyamide 6 + ABS

General Information

Product Description

PA6/ABS blend, 8% glass fibre injection moulding grade. Toughened. Natural colour.

Suitable for parts requiring improved stiffness, along with improved impact resistance. Excellent aesthetic surface aspect.

General		
Filler / Reinforcement	• Glass Fiber, 8.0% Filler by Weight	
Additive	• Impact Modifier	
Features	• Good Impact Resistance • Good Stiffness	• Impact Modified • Outstanding Surface Finish
Agency Ratings	• EU 2011/65/EC	
RoHS Compliance	• RoHS Compliant	
Appearance	• Natural Color	
Processing Method	• Injection Molding	
Resin ID (ISO 1043)	• (PA6+ABS)-I-GF8	

Properties [1]

Physical	Dry	Conditioned	Unit	Test Method
Density	1.13	--	g/cm³	ISO 1183
Water Absorption				ISO 62
Saturation, 73°F, 0.0787 in	5.3	--	%	
Water Absorption				ISO 62
Equilibrium, 73°F, 0.0787 in, 50% RH	1.7	--	%	
Mechanical	**Dry**	**Conditioned**	**Unit**	**Test Method**
Tensile Modulus	580000	363000	psi	ISO 527-1/1A/1
Tensile Stress (Yield)	10900	7980	psi	ISO 527-2/1A/50
Tensile Strain (Yield)	4.0	6.0	%	ISO 527-2/1A/50
Nominal Tensile Strain at Break	6.0	20	%	ISO 527-2/1A/50
Flexural Modulus [2]	493000	326000	psi	ISO 178
Flexural Stress [2]	17400	10900	psi	ISO 178
Impact	**Dry**	**Conditioned**	**Unit**	**Test Method**
Charpy Notched Impact Strength				ISO 179/1eA
73°F	5.5	--	ft·lb/in²	
Charpy Unnotched Impact Strength				ISO 179/1eU
73°F	29	36	ft·lb/in²	
Thermal	**Dry**	**Conditioned**	**Unit**	**Test Method**
Vicat Softening Temperature	302	--	°F	ISO 306/B50
Melting Temperature [3]	432	--	°F	ISO 11357-3

Radilon® MIXLOY S RVA80T 100 NT

Radici Group High Performance Polymers - Polyamide 6 + ABS

Processing Information		
Injection	**Dry**	**Unit**
Drying Temperature - Desiccant Dryer	176	°F
Drying Time - Desiccant Dryer	2.0 to 4.0	hr
Dew Point - Desiccant Dryer	< -4	°F
Suggested Max Moisture	0.15	%
Processing (Melt) Temp	464 to 500	°F
Mold Temperature	104 to 140	°F
Injection Rate	Moderate	

Notes

[1] Typical properties: these are not to be construed as specifications.

[2] 0.079 in/min

[3] 10°C/min