

DURACON® TR-20LV

Polyplastics - Acetal (POM) Copolymer

General Information

Product Description

Low VOC

Mineral Reinforced

General

Filler / Reinforcement	• Mineral
Features	• Copolymer • Low VOC
UL File Number	• E45034
Forms	• Pellets
Processing Method	• Injection Molding
Part Marking Code (ISO 11469)	• >POM-TD15<

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density	1.53	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	22	g/10 min	ISO 1133
Melt Volume-Flow Rate (MVR) (190°C/2.16 kg)	17	cm ³ /10min	ISO 1133
Molding Shrinkage ²			ISO 294-4
Across Flow : 0.0787 in	1.7	%	
Flow : 0.0787 in	1.8	%	
Water Absorption (24 hr, 73°F, 0.0394 in)	0.50	%	ISO 62
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	616000	psi	ISO 527-1
Tensile Stress	7980	psi	ISO 527-2
Tensile Strain (Break)	8.0	%	ISO 527-2
Flexural Modulus	566000	psi	ISO 178
Flexural Stress	13100	psi	ISO 178
Coefficient of Friction			JIS K7218
Dynamic ³	0.40		
vs. Steel - Dynamic ⁴	0.50		
Wear Factor			JIS K7218
71 psi, 59 ft/min ⁵	5.0	10 ⁻¹⁰ in ³ ·min/ft·lb·hr	
8.7 psi, 30 ft/min ⁶	250	10 ⁻¹⁰ in ³ ·min/ft·lb·hr	
71 psi, 59 ft/min ⁷	1500	10 ⁻¹⁰ in ³ ·min/ft·lb·hr	
8.7 psi, 30 ft/min ⁸	4500	10 ⁻¹⁰ in ³ ·min/ft·lb·hr	
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (73°F)	1.4	ft·lb/in ²	ISO 179/1eA
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	75		ISO 2039-2

DURACON® TR-20LV

Polyplastics - Acetal (POM) Copolymer

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load 264 psi, Unannealed	253	°F	ISO 75-2/A
CLTE - Flow (73 to 131°F)	4.4E-5	in/in/°F	Internal Method
CLTE - Transverse (73 to 131°F)	4.4E-5	in/in/°F	Internal Method
Flammability	Nominal Value	Unit	Test Method
Flame Rating	HB		UL 94
Additional Information	Nominal Value	Unit	
Color Number	CF2001		

Notes

¹ Typical properties: these are not to be construed as specifications.

² 60×60×2mmt, Cavity Pressure 60 MPa

³ vs M90-44, 0.06 MPa, 15 cm/s

⁴ 0.49 MPa, 30 cm/s

⁵ vs C-Steel, Steel Side

⁶ vs M90-44, Material Side

⁷ vs C-Steel, Material Side

⁸ vs M90-44, M90-44 Side